

300 Series
Engine & Equipment
Model

6.329

277,549 >

O'rings on block

Large Pin

6 Cyl

Bore: 4.02 in
 102 mm
 Pin Ø: 1.375 in
 35 mm
















APPLICATIONS:

AGRICULTURAL

499 3530
 950 4030
 960 4400
 2840 4425
 3130

CONSTRUCTION

444
 444C
 444D
 444CH
 544A
 570A
 710B

				
1) Engine O/H Kit	Piston-Liner Kit	Main Bearing	Thrust Bearing	Con Rod Bearing
2) Engine I/F Kit	TAR78041 Consists of:	TRE27352 Std.	TAT21139 Std.	TRE27348 Std.
1) TAT86986	a) TAR77762	TRE27353 .010	TAT21132 .010	TRE27349 .010
2) TIK86986	b) TAR55759	TRE27360 .020	TAT21134 .020	TRE27358 .020
	c) TR125754	TRE27368 .030	TAT21136 .030	TRE27364 .030
	d) TR116463			
	e) TAR71618			
	f) TM41029	Use 6	Use 1	Use 6
				
1) Front Seal 2) Rear Seal	1) O/H Gasket Set	1) Bush, Con Rod 2) Bolt, Con Rod	1) Pump, Oil 2) Oil Cooler 3) Rocker Arm 4) Rocker Shaft 5) Pump, Oil Tube	1) Lower Gear 2) Lower Bushing 3) Upper Gear 4) Upper Bushing 5) Cam. Follower 6) Cam. Gear
3) Crankshaft 4) Crankshaft, Gear 5) Ring Gear	2) Head Gasket Set 3) Head Gasket 4) Oil Pan Gasket 5) Rocker Cover Gsk	3) Camshaft 4) Con Rod		
1) TAR67942 2) TRE44574 3) TAT22562 4) TT20094 5) TR114282 (142T)	1) TRE501580 2) TRE38852 3) TR114157 4) TR97344 (1) 5) TR75728	1) TR55647 x6 2) TR74194 x12 3) TR82821 (2) 4) TRE16495 (3)	1) TRE55343 2) TRE31929 3) TRE31973 4) TR54986 5) TR113752	1) TAT24252 2) TT26321 3) TAT18009 4) TT20034 5) TT20073 6) TT20070
	Valve, Intake	Valve, Exhaust	Insert, Valve 1) Intake 2) Exhaust	1) Cap, Valve 2) Lock, Valve 1) Spring, Valve 2) Rotator, Valve 3) O'ring, Valve
	TR79623 Std. TR79628 .003 TR79629 .015	TR79624 Std. TR79625 .003 TR79626 .015	1) TR73064 Std. 2) TR51734 Std.	1) TT20129 2) TT20077 1) TR26125 2) TRE11410 3) TR87627
				
Thermostats	Fuel Transfer Pump	Water Pump Repair Kit		Injector, Pencil
TAR70601 180 °F (*) TAR77411 195 °F (*) TRE33705 180 °F (*)	TRE42211	Without Impeller	With Impeller	Seal
		TMX9398	TMX131	TAR89564
				TR60746 TR48000

(*) Verify JD manual.

(1) For Tractor Model 4030 order [TR97345](#).

(2) Threaded Type.

(3) For Connecting Rods RE16495 and RE21076 Use Connecting Rod Bolt [TR80033](#).