

















300 Series Engine & Equipment Model						
6068D Liter Designated Large Pin 6 Cyl Bore: 4.19 in 106.5 mm Pin Ø: 1.62 in 41 mm	1) Engine O/H Kit	Piston-Liner Kit	Main Bearing	Thrust Bearing	Con Rod Bearing	
	2) Engine I/F Kit	TRE28966 Consists of:	TRE27352 Std.	TAT21139 Std.	TAR97517 Std.	
	1) TOK3694	a) TRE28919	TRE27353 .010	TAT21132 .010	TAR97653 .010	
	2) TIK3694	b) TRE66820 c) TR124230 d) TR80500 e) TAR65507 f) TR54114	TRE27360 .020 TRE27368 .030	TAT21134 .020 TAT21136 .030	TAR97654 .020 TAR97655 .030	
			Use 6	Use 1	Use 6	
APPLICATIONS: AGRICULTURAL 6506 OEM Marine Ag Construction						
	1) Front Seal 2) Rear Seal	1) O/H Gasket Set	1) Bush, Con Rod 2) Bolt, Con Rod	1) Pump, Oil 2) Cyl Hd Cap Screw	1) Lower Gear 2) Lower Bushing 3) Upper Gear 4) Upper Bushing 5) Cam. Follower 6) Cam. Gear	
	3) Crankshaft 4) Crankshaft, Gear 5) Ring Gear 6) Sleeve, Front 7) Packing, Sleeve	2) Head Gasket Set 3) Head Gasket 4) Oil Pan Gasket 5) Rocker Cover Gsk	3) Camshaft			
	1) TAR67942 2) TRE44574 3) TRE45517 (3) 4) TT20094 5) TR28811 (129T) or TR114282 (142T) 6) TR81989 7) TH35244	1) TRE501580 2) TRE38852 3) TR114157 4) TR97344 5) TR75728	1) TR57451 x6 2) TR74195 x12 (5) 3) TR82821 (2)	1) TRE65580 2) TR85363 x26 (4)	1) TAT24252 (1) 2) TT26321 3) TAT18009 (1) 4) TT20034 5) TT20073 6) TT20070 (1)	
	Valve, Intake	Valve, Exhaust	Insert, Valve 1) Intake 2) Exhaust	1) Seal, Valve 2) Lock, Valve	1) Spring, Valve 2) Rotator, Valve	
	TR98062 Std. TR97490 .015	TR90692 Std. TR97492 .015	1) TR98063 Std. TR98335 O/S 2) TR85687 Std. TR93910 O/S	1) TRE31617 2) TR91889	1) TR26125 2) TRE60005	
	Thermostat					
TRE64354 180° F	TRE42211	Without Impeller TRE19510	With Impeller TRE11348	TRE41157	1) Seal, Injector 2) Injector, Pencil 1) TR60746 TR48000 2) TRE38087	

(1) Helicoidal Gears.
 (2) Threaded Type.
 (3) Crankshaft (m) R104523.
 (4) Replace all R78558 Cap Screws with Flanged Head Cap Screw **TR85363**.
 (5) When used on connecting rods marked R56187, torque bolts to 95 ft.lbs. Only.