

400 Series
Engine & Equipment
Model

6.466A

233,593-317,858

6 Cyl

Bore: 4.56 in
 116 mm
 Pin Ø: 1.85 in
 47 mm

Con Rod (m):
 R71074 (P/N AR93341)


APPLICATIONS:

AGRICULTURAL

4840 8440
 4850 8450
 5720 8820
 5730 9940
 8430 9950

CONSTRUCTION

644C 770A/B
 690C 850B
 740A 892D
 762A/B

1) Engine O/H Kit	Piston-Liner Kit	Main Bearing	Thrust Bearing	Con Rod Bearing
2) Engine I/F Kit	TAR100960 Consists of:	TAR74814 Std. TAR74816 .010 TAR74817 .020 TAR74818 .030	TAR77748 Std. TAR77750 .010 TAR77751 .020 TAR77752 .030	TAR73277 Std. TAR73279 .010 TAR73280 .020 TAR73281 .030
1) TRG20142	a) TAR100673	Use 6	Use 1	Use 6
2) TIK20142	b) TRE48380			
	c) TR57771	Use 6	Use 1	Use 6
	d) TAR63060			
	e) TAR98850	Use 6	Use 1	Use 6
	f) TE1343FN			
1) Front Seal 2) Rear Seal	1) O/H Gasket Set	1) Bush, Con Rod 2) Bolt, Con Rod 3) Bushing, Cam	1) Cam Follower 2) Oil Cooler 3) Camshaft Kit 4) Plug, Camshaft 5) O'ring, Oil Cooler 6) Head Bolt, Kit	1) Pump, Oil 2) Repair Kit
3) Crankshaft 4) Crankshaft, Gear 5) Ring Gear 6) Rear Gear	2) Head Gasket Set 3) Head Gasket 4) Oil Pan Gasket	4) Con Rod		
1) TAR49025 2) TRE520036 3) TRE53422 (6) 4) TR26049 (23T) 5) TR28811 (129T) 6) TR63326	1) TAR98845 2) TAR98851 3) TRE47336 4) TR71918	1) TR74008 x6 2) TR66452 x12 3) TR46903 x4 4) TAR93341 x1  (1)	1) TR52773 2) TAT25038 (5) 3) TAR100385 4) TR26115 5) TR47153 6) TMX365 (3)* TMX366 (4)**	1) TRE60622 2) TMX1062 (2)
	Valve, Intake	Valve, Exhaust	Insert, Valve 1) Intake 2) Exhaust	1) Cap, Valve 2) Lock, Valve
	TR50358 Std. TR55055 .003 TR55057 .015	TR50357 Std. TR55056 .003 TR55058 .015	1) TR78702 Std. 2) TR50356 Std.	1) TT20129 2) TT20077
				1) TR26125 2) TRE11410 3) TR87627
TAR48675 180° F	Not Used	Without Impeller	With Impeller	1) TRE55985 (m) R71224, (m) R83561 2) TRE20022 (OEM ESN 067685 >)
See Chart				

(1) Shape, Conrod Bushing.
 (2) For Crankshaft driven Engine Pump, Oil Consists of: Shaft, Gears, and Gaskets.
 (3) **TMX365** Consists of: **TR88042 x6, TR88043 x5, TR88044 x8, TR88045 x7.** * With ESN > 317676.
 (4) **TMX366** Consists of: **TR88043 x11, TR88044 x8, TR88045 x7.** ** With ESN 317677 >.
 (5) Some applications use **TAR55394.**

(6) **TRE53422** will require front key **TR116311** for the front damper.